

TECHNICAL DATA SHEET ATG110SP – VEGETABLE OIL GENERATOR

DESCRIPTION

1. STRUCTURE

- Runs with Straight Vegetable Oil (SVO, e.g. rape oil, soya oil, sun flower oil, palm oil, jatropha oil, ...), Waste Vegetable Oil (WVO) or common Diesel fuel
- Easy to use by means of fully automatic PLC-control, supports local or remote operation
- Suitable as backup system for solar and wind power plants
- SUPERSILENCED (70 dB(A)±3 at 7 mt.)
- Engine/alternator monoblock unit coupled through flexi-disc couplings, installed on a welded steel baseframe, complete with antivibration mountings
- Soundproof canopy that can be opened in two section, made of 20/10 sheet steel, soundproof material, internal silencer, handles and stay rod, internal fuel tank cap, pull-out lifting hook
- Industrial painting in RAL 1004 (golden yellow)
- Integrated daily-service diesel fuel tank - 140 litres, vegetable oil tank connected external (not included)
- Fuel consumption at 75% of load: approx. 17.1 L/h
- Lead acid batteries: 12 V / 145 Ah
- Dimensions (mm): L= 2850 x W= 1000 x H= 1400 - weight (Kilos): 1620

2. ELECTRIC START PANEL

- Earth fault device
- Magnetothermic circuit breaker
- Socket 32A 230V, Socket 32A 400V
- Voltmeter + phase selector switch
- Ammeter, Frequency meter, Hours run meter
- Engine safety device: high water temperature, low oil pressure, battery charger fault
- Low fuel level switch
- Emergency stop button

TECHNICAL DATA

1. EQUIPMENT SPECIFICATION (according ISO 8528/1)

- Standby power at cosfi 0.8 : 110 kVA
- Prime power at cosfi 0.8 : 100 kVA
- Standby power at cosfi 0.8 : 88 kW
- Prime power at cosfi 0.8 : 80 kW
- Frequency : 50 Hz
- Voltage available to the terminals : 400/230 V

2. ENGINE

- 4 stroke motor - water cooled
- Brand and model : PERKINS 1104C-44
- Governor : mechanical
- Max power : 138 hp
- R.P.M. : 1500
- Cylinders : 4
- Displacement : 4410 cc
- Emission standard : Stage 2

3. ALTERNATOR

- Synchronous generator with electronic governor and AVR (Automatic Voltage Regulator)
- Brand and model : MECC-ALTE ECP34-2S/4 (OR SIMILAR BRAND)
- Poles : 4
- Stator/rotator insulation : Class H
- Protection level : IP21
- Continuous power (50 Hz) : 105 kVA

